

product_datasheet_title

HALOLINE PRO 48 W 230 V R7S

HALOLINE® PRO | Double ended halogen lamps with tube base




technical_data

ELECTRICAL DATA

Nominal wattage	48 W
Construction wattage	48.00 W
Nominal voltage	230 V
Claimed equiv. conventional lamp power	60 W

PHOTOMETRICAL DATA

Luminous flux	700 lm
Luminous efficacy	14 lm/W
Light color (designation)	Warm White
Color temperature	2800 K
Color rendering index Ra	100
Light color	1028
UV protection	No



349635_HAL_ohne_UVS

LIGHT TECHNICAL DATA

Starting time	0 s
---------------	-----

DIMENSIONS & WEIGHT

Overall length	74.90 mm
Diameter	12.00 mm
Product weight	5.5 g

ADDITIONAL PRODUCT DATA

Base (standard designation)	R7s
Mercury-free	Yes

Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required / Technical and light values are subject to be changed

CAPABILITIES

Dimmable	yes
Burning position	Any

CERTIFICATES & STANDARDS

Energy efficiency class	G
Energy consumption	48.00 kWh/1000h


COUNTRY-SPECIFIC CATEGORIZATIONS

ILCOS	HDG-48-230-R7s-74,9
Order reference	64684 ECO

Energy labelling regulation data

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	no
Color-tuneable light source	no
Envelope	No
High luminance light source	no
Anti-glare shield	no
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	74.90 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.406
Beam angle correspondence	SPHERE_360
EPREL ID	714446,1635406
Model number	AC35327,AC54063

download_data

Photometric and lighting design files	document_name
 Spectral power distribution	349635_HAL_ohne_UVS

logistical_data

product_code	packaging_unit	dimensions	weight	volume
4008321977595	Folding box 1	87 mm x 18 mm x 21 mm	9.10 g	0.03 dm ³
4008321977601	Shipping box 20	92 mm x 77 mm x 113 mm	223.00 g	0.80 dm ³
4052899401068	Shipping box 720			
4099854179280	Shipping box 720	347 mm x 323 mm x 385 mm	8487.00 g	43.15 dm ³

logistical_data_text

disclaimer_title

disclaimer_text